



2025 Ram Heavy Duty SPECIFICATIONS

Specifications are based on the latest product information available at the time of publication.

All dimensions are in inches (millimeters) unless otherwise noted.

All dimensions measured at curb weight with standard tires and wheels.

GENERAL INFORMATION

Vehicle Type	Regular Cab, Crew Cab and Mega Cab: 4x2, 4x4
Assembly Plant	Saltillo Truck Assembly Plant, Coahuila, Mexico
EPA Vehicle Class	Standard Pickup

BODY/CHASSIS

Model	4x2	4x4
Layout	Longitudinal, front engine	Longitudinal, front engine, transfer case
Construction	Ladder-type frame, steel cab, double-wall steel pickup box	Ladder-type frame, steel cab, double-wall steel pickup box

ENGINE: 6.4-LITER HEMI® V-8

Type and Description	90-degree gasoline V-8 with variable cam timing
Displacement	392 cu. in. (6,417 cu. cm)
Bore x Stroke	4.09 x 3.72 (103.9 x 94.6)
Valve System	Pushrod-operated overhead valves, 16 valves, eight deactivating and eight hydraulic lifters, all with roller followers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, 356 aluminum cylinder heads with hemispherical combustion chambers
Compression Ratio	10.0:1
Power	405 hp (306 kW) @ 5,600 rpm
Torque	429 lb.-ft. (582 N•m) at 4,000 rpm
Maximum Engine Speed	5,800 rpm limited
Fuel Requirement	Unleaded regular, 87 octane
Oil Capacity	7.0 quarts (6.6 liters)



ENGINE: 6.4-LITER HEMI® V-8 (continued)

Coolant Capacity	16.6 quarts (15.75 liters)
Emission Controls	Three-way catalytic converters, heated oxygen sensors, cooled electronic exhaust-gas recirculation (EGR) and individual cylinder fuel control

ENGINE: 6.7-LITER CUMMINS TURBO DIESEL I-6 (High Output)

Type And Description	Inline six cylinder, turbocharged, intercooled diesel
Displacement	408 cu. in. (6,690 cu. cm)
Bore x Stroke	4.21 x 4.88 (107 x 124)
Valve System	Pushrod-operated overhead valves, 24 valves, hydraulic lifters
Fuel Injection	Electronic high-pressure common rail
Construction	Compacted graphite iron (CGI) block cast-iron head
Compression Ratio	16.2:1
Power	430 hp (313 kW) @ 2,800 rpm
Torque	1,075 lb.-ft. (1,458 N•m) @ 1,800 rpm
Maximum High-Idle Engine Speed	3,200 rpm
Fuel Requirement	Ultra-low sulfur diesel
Oil Capacity	12.0 quarts (11.3 liters) with filter
Coolant Capacity	23.8 quarts (22.50 liters)
Emission Controls	Selective catalytic reduction (SCR)

TRANSMISSION: ZF TORQUEFLITE HD 8HP75 — AUTOMATIC EIGHT-SPEED

Availability	6.4-liter HEMI V-8
Description	Adaptive electronic control, automatic or Electronic Range Select (ERS) manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear

Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.10
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67



TRANSMISSION: ZF TORQUEFLITE HD 8HP75 — AUTOMATIC EIGHT-SPEED (continued)

Reverse	3.30
Axle Gear Ratios	3.73, 4.10

TRANSMISSION: ZF TORQUEFLITE HD 8AP1075 — AUTOMATIC EIGHT-SPEED

Availability	6.7-liter I-6 Cummins turbo diesel
Description	Adaptive electronic control, automatic or Electronic Range Select (ERS) manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear
Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.10
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Axle Gear Ratios	3.42

TRANSFER CASE: BW 44-46, BW 44-47

Availability	Optional on 6.4-liter HEMI V-8
Type	Part-time BW 44-46 electric shift
Operating Modes	2WD; 4WD High; Neutral; 4WD Low
Low-Range Ratio	2.64
Center Differential	None

TRANSFER CASE: BW 44-48

Availability	6.7-liter diesel high output
Type	44-48 part-time with electric shift
Operating Modes	2WD; 4WD High; Neutral; 4WD Low
Low-Range Ratio	2.64
Center Differential	None



AXLES

Front (4x4)	AAM 9.25-in. beam front axle with center disconnect (locking differentials on Power Wagon)
Rear	AAM 11.5-in. beam rear axle (2500 and 3500 limited-slip and locking differentials on Power Wagon) AAM 12.0-in. beam rear axle (3500 Max Tow)

ELECTRICAL SYSTEM

Alternator	
Rating	180-amp included with 6.4-liter HEMI V-8 and 6.7-liter diesel 220-amp included with 6.7-liter Laramie, Longhorn and Limited
Rating	Dual (220 and 180) optional on 6.4-liter HEMI V-8
Rating	Dual 220-amp optional on 6.7-liter diesel
Battery	
Description	Group 65, maintenance-free, 730 CCA on 6.4-liter HEMI V-8 Dual Group 65, maintenance-free, 730 CCA on 6.7-liter diesel

SUSPENSION 2500

Model	4x2	4x4
Front	Three-link with track bar, coil springs, stabilizer bar, solid axle	Three-link with track bar, coil springs, stabilizer bar, solid axle, disconnecting sway bar (Power Wagon only)
Rear	Five-link with track bar, coil springs, stabilizer bar, solid axle	Five-link with track bar, coil springs, stabilizer bar, solid axle (optional air bags)

SUSPENSION 3500

Model	4x2	4x4
Front	Three-link with track bar, coil springs, stabilizer bar, solid axle	Three-link with track bar, coil springs, stabilizer bar, solid axle
Rear	Two-stage longitudinal leaf (optional supplemental air bags) solid axle	Two-stage longitudinal leaf (optional supplemental air bags) solid axle



BRAKES

Front

Size and Type	14.17 x 1.54 (359.9 x 39.1) disc with twin-piston pin-slider caliper and ABS
---------------	--

Rear

Size and Type	14.09 x 1.34 (357.9 x 34.0) disc with twin-piston pin-slider caliper and ABS
---------------	--

Power-Assist Type	Dual-rate, tandem diaphragm vacuum (2500 gas) Hydro-boost (2500 diesel and all 3500)
-------------------	---

AIR BAGS

Regular Cab	6
Crew Cab	6
Mega Cab	6

STEERING

Power Assist	Hydraulic assist
--------------	------------------

CARGO BOX

NOMINAL BOX SIZE	6-FT. 4-IN. (CREW OR MEGA)	8-FT. (REGULAR OR CREW)
SAE Volume, cu. ft. (cu. m)	57.5 (1.6)	74.7 (2.1)
Length at Floor, Tailgate Closed	76.3 (1,938.5)	98.3 (2,496.5)
Cargo Width	66.4 (1,686.9)	66.4 (1,686.9)
Distance Between Wheelhouses	51 (1,295.4)	51 (1,295.4)
Depth	20.1 (511.1)	20.2 (513.0)
Tailgate Opening Width	60.4 (1,535.3)	60.4 (1,535.3)

EXTERIOR DIMENSIONS

REGULAR CAB 140.5-IN. WB, 8-FT. BOX (2500)

Regular Cab 140.5-in. WB, 8-ft. Box (2500)	4x2	4x4
Wheelbase	140.2 (3,560)	140.2 (3,560)
Track Width — Front	68.7 (1,745)	68.7 (1,745)



Regular Cab

140.5-in. WB, 8-ft. Box (2500)

	4x2	4x4
Track Width — Rear	68.1 (1,729)	68.1 (1,729)
Overall Length	232 (5,892)	232 (5,892)
Overall Width @ SgRp Front	83.5 (2,120)	83.5 (2,120)
Overall Height	78 (1,981)	80.2 (2,037)
Suspension or Axle to Ground — Front	7.3 (184)	9.3 (237)
Suspension or Axle to Ground — Rear	8.4 (212)	8.5 (217)
Approach Angle (Degrees)	18.8	22.8
Ramp Breakover Angle (Degrees)	20.8	23.9
Departure Angle (Degrees)	22.9	29.9
Ground Clearance	13 (332)	13.1 (333)
Turning Diameter	45.4 (13.8)	45.5 (13.9)

CREW CAB 149.5-IN. WB, 6-FT. 4-IN. BOX (2500)

Crew Cab

149.5-in. WB, 6-ft. 4-in. Box (2500)

	4x2	4x4
Wheelbase	149 (3,785)	149 (3,785)
Track Width — Front	68.7 (1,745)	68.7 (1,745)
Track Width — Rear	68.1 (1,729)	68.1 (1,729)
Overall Length	238.8 (6,066)	238.8 (6,067)
Overall Width @ SgRp Front	83.5 (2,120)	83.5 (2,120)
Overall Height	78.2 (1,987)	80.2 (2,037)
Suspension or Axle to Ground — Front	7.4 (188)	9.3 (236)
Suspension or Axle to Ground — Rear	8.5 (216)	8.5 (217)
Approach Angle (Degrees)	18.8	22.9
Ramp Breakover Angle (Degrees)	20.3	23.9
Departure Angle (Degrees)	23.6	25.8
Ground Clearance	11.1 (281)	13.1 (333)
Turning Diameter	14.6 (47.9)	14.6 (47.9)



CREW CAB 169.5-IN. WB, 8-FT. BOX (2500)

Crew Cab 169.5-in. WB, 8-ft. Box (2500)	4x2	4x4
Wheelbase	169 (4,293)	169 (4,293)
Track Width — Front	68.7 (1,734.8)	68.7 (1,745)
Track Width — Rear	68.1 (1,729)	68.1 (1,729)
Overall Length	260.8 (6,626)	260.8 (6,626)
Overall Width @ SgRp Front	83.5 (2,120)	83.5 (2,120)
Overall Height	78.1 (1,983)	80.1 (2,035)
Suspension or Axle to Ground — Front	7.3 (185)	9.4 (237)
Suspension or Axle to Ground — Rear	9.9 (253)	8.6 (218)
Approach Angle (Degrees)	18.7	23.2
Ramp Breakover Angle (Degrees)	19.1	22.7
Departure Angle (Degrees)	22.5	24.7
Ground Clearance	11.1 (282)	13.1 (334)
Turning Diameter	16.3 (53.5)	16.3 (53.5)

POWER WAGON & REBEL CREW CAB 149.3-IN. WB, 6-FT. 4-IN. BOX

Power Wagon & Rebel Crew Cab 149.3-in. WB, 6-ft. 4-in. Box	4x2	4x4
Wheelbase	NA	149.3 (3,792)
Track Width — Front	NA	68.7 (1,745)
Track Width — Rear	NA	68.1 (1,729)
Overall Length	NA	238.8 (6,067)
Overall Width @ SgRp Front	NA	83.4 (2,119)
Overall Height	NA	80.9 (2,054)
Suspension or Axle to Ground — Front	NA	8.3 (210)
Suspension or Axle to Ground — Rear	NA	8.3 (210)
Approach Angle (Degrees)	NA	29.4 (26.6 — Rebel)
Ramp Breakover Angle (Degrees)	NA	22 (21.8 — Rebel)



Power Wagon & Rebel Crew Cab

149.3-in. WB, 6-ft. 4-in. Box

	4x2	4x4
Departure Angle (Degrees)	NA	26
Ground Clearance	NA	14.2 (360) (13.3./339 — Rebel)
Turning Diameter	NA	14.7 (48.2)

MEGA CAB 160.5-IN. WB, 6-FT. 4-IN. BOX (2500)

Mega Cab

160.5-in. WB, 6-ft. 4-in. Box (2500)

	4x2	4x4
Wheelbase	NA	160.4 (4,074)
Track Width — Front	NA	68.7 (1,745)
Track Width — Rear	NA	68.1 (1,729)
Overall Length	NA	249.9 (6,348)
Overall Width @ SgRp Front	NA	83.5 (2,120)
Overall Height	NA	80.1 (2,036)
Suspension or Axle to Ground — Front	NA	9.4 (238)
Suspension or Axle to Ground — Rear	NA	8.5 (217)
Approach Angle (Degrees)	NA	23.3
Ramp Breakover Angle (Degrees)	NA	23.2
Departure Angle (Degrees)	NA	25.7
Ground Clearance	NA	13.1 (334)
Turning Diameter	NA	15.6 (51.2)

REGULAR CAB 140.5-IN. WB, 8-FT. BOX (3500)

Regular Cab

140.5-in. WB, 8-ft. Box (3500)

	4x2	4x4
Wheelbase	140.2 (3,560)	140.2 (3,560)
Track Width — Front	67.7 (1,719) 69.6 (1,769) DRW	67.7 (1,719) 69.6 (1,769) DRW
Track Width — Rear	67.1 (1,703) 75.9 (1,927) DRW	67.1 (1,703) 75.9 (1,927) DRW



Regular Cab

140.5-in. WB, 8-ft. Box (3500)

	4x2	4x4
Overall Length	232 (5,892)	232 (5,892)
Overall Width @ SgRp Front	83.5 (2,120) 96.5 (2,450) DRW	83.5 (2,120) 96.5 (2,450) DRW
Overall Height	77.8 (1,976)	79.5 (2,019)
Suspension or Axle to Ground — Front	7.4 (188) 6.6 (168) DRW	9.3 (237) 8.5 (216) DRW
Suspension or Axle to Ground — Rear	7.9 (209) 8.2 (208) DRW	8.5 (217) 8.4 (213) DRW
Approach Angle (Degrees)	18.2 16.6 DRW	23.2 20.6 DRW
Ramp Breakover Angle (Degrees)	21.8 19.7 DRW	25.2 23.2 DRW
Departure Angle (Degrees)	25.4 23.6 DRW	25.2 24.4 DRW
Ground Clearance	11.2 (286) 10.6 (269) DRW	13.3 (338) 12.4 (314) DRW
Turning Diameter	13.8 (45.4)	13.9 (45.5)

CREW CAB 169.5-IN. WB, 8-FT. BOX (3500)

Crew Cab

169.5-in. WB, 8-ft. Box (3500)

	4x2	4x4
Wheelbase	169.1 (4,294)	169.3 (4,300)
Track Width — Front	67.7 (1,719) 69.6 (1,769) DRW	67.7 (1,719) 69.6 (1,769) DRW
Track Width — Rear	67.1 (1,703) 75.9 (1,927) DRW	67.1 (1,703) 75.9 (1,927) DRW
Overall Length	260.8 (6,626)	260.8 (6,626)
Overall Width @ SgRp Front	83.5 (2,120) 96.5 (2,450) DRW	83.5 (2,120) 96.5 (2,450) DRW
Overall Height	78.4 (1,990) 77.1 (1,959) DRW	78.4 (1,990) 79.3 (2,015) DRW



Crew Cab

169.5-in. WB, 8-ft. Box (3500)

	4x2	4x4
Suspension or Axle to Ground — Front	7.3 (186)	7.3 (186)
	6.4 (162) DRW	8.4 (214) DRW
Suspension or Axle to Ground — Rear	9.0 (228)	9.0 (228)
	6.4 (162) DRW	9.3 (236) DRW
Approach Angle (Degrees)	18.3	23.3
	16.9 DRW	20.6 DRW
Ramp Breakover Angle (Degrees)	19.5	22.4
	17.3 DRW	21.3 DRW
Departure Angle (Degrees)	24.2	23.5
	21.2 DRW	24.2 DRW
Ground Clearance	11.2 (285)	11.5 (290)
	10.2 (260) DRW	12.3 (312) DRW
Turning Diameter	16.3 (53.6)	16.4 (53.7)

MEGA CAB 160.5-IN. WB, 6-FT. 4-IN. BOX (3500)

Mega Cab

160.5-in. WB, 6-ft. 4-in. Box (3500)

	4x2	4x4
Wheelbase	NA	160.4 (4,074)
Track Width — Front	NA	67.7 (1,719)
		69.6 (1,769) DRW
Track Width — Rear	NA	67.1 (1,704)
		75.9 (1,927) DRW
Overall Length	NA	249.9 (6,348)
Overall Width @ SgRp Front	NA	83.5 (1,994)
		96.5 (2,450) DRW
Overall Height	NA	78.5 (2,036)
		78.9 (2,004) DRW
Suspension or Axle to Ground — Front	NA	7.3 (187)
		8.4 (214) DRW
Suspension or Axle to Ground — Rear	NA	8.3 (210)
		6.8 (174) DRW



Mega Cab

160.5-in. WB, 6-ft. 4-in. Box (3500)

	4x2	4x4
Approach Angle (Degrees)	NA	18.5 21.7 DRW
Ramp Breakover Angle (Degrees)	NA	20.3 21.5 DRW
Departure Angle (Degrees)	NA	25.7 23.1 DRW

INTERIOR DIMENSIONS

ACCOMMODATIONS (Model, Seating Capacity, F/R)

Front	Regular Cab	Crew Cab	Mega Cab
Seating	3/0 or 2/0	3/3 or 2/3	3/3 or 2/3
Headroom	39.8 (1,011)	40.9 (1,038)	40.9 (1,038)
Legroom	40.9 (1,040)	40.9 (1,040)	40.9 (1,040)
Shoulder Room	65.9 (1,675)	65.9 (1,675)	65.9 (1,675)
Hip Room	62.9 (1,598)	62.9 (1,598)	62.9 (1,598)

Rear	Regular Cab	Crew Cab	Mega Cab
Headroom	NA	39.8 (1,010)	40.3 (1,023)
Legroom	NA	40.2 (1,022)	43.1 (1,096)
Shoulder Room	NA	65.6 (1,666)	65.6 (1,667)
Hip Room	NA	62.7 (1,593)	62.8 (1,595)

INTERIOR VOLUME

Interior Volume	Regular Cab	Crew Cab	Mega Cab
Front — cu. ft. (cu. m)	62.5 (1.8)	63.9 (1.8)	63.9 (1.8)
Rear — cu. ft. (cu. m)	NA	60.7 (1.7)	66 (1.9)

###