



2025 Ram Chassis Cab

SPECIFICATIONS

Specifications are based on the latest product information available at the time of publication.

All dimensions are in inches (millimeters) unless otherwise noted.

All dimensions measured at curb weight with standard tires and wheels.

GENERAL INFORMATION

Vehicle Type	Regular Cab, Crew Cab: 4x2, 4x4
Assembly Plant	Saltillo Truck Assembly Plant, Coahuila, Mexico

BODY/CHASSIS

Model	4x2	4x4
Layout	Longitudinal, front engine	Longitudinal, front engine, transfer case
Construction	Ladder-type frame, steel cab	Ladder-type frame, steel cab

ENGINE: 6.4-LITER HEMI V-8

Type and Description	90-degree gasoline V-8 with variable cam timing
Displacement	392 cu. in. (6,417 cu. cm)
Bore x Stroke	4.09 x 3.72 (103.9 x 94.6)
Valve System	Pushrod-operated overhead valves, 16 valves, eight de-activating and eight hydraulic lifters, all with roller followers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, 356 aluminum cylinder heads with hemispherical combustion chambers
Compression Ratio	10.0:1
Power	375 hp (306 Kw) @ 5,600 rpm
Torque	429 lb.-ft. (582 N•m) @ 4,000 rpm
Maximum Engine Speed	5,800 rpm limited
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	7.0 quarts (6.6 liters)
Coolant Capacity	16.6 quarts (15.75 liters)
Emission Controls	Three-way catalytic converters, heated oxygen sensors, cooled electronic exhaust-gas recirculation (EGR) and individual cylinder fuel control



ENGINE: 6.7-LITER CUMMINS TURBO DIESEL I-6

Type and Description	Inline six-cylinder turbocharged, intercooled diesel
Displacement	408 cu. in. (6,690 cu. cm)
Bore x Stroke	4.21 x 4.88 (107 x 124)
Valve System	Pushrod-operated overhead valves, 24 valves, hydraulic lifters
Fuel Injection	Electronic high-pressure common rail
Construction	Compacted graphite iron (CGI) block cast-iron head
Compression Ratio	16.2:1
Power	360 hp (268 Kw) @ 2,800 rpm
Torque	800 lb.-ft. (1,084 N•m) @ 1,800 rpm
Maximum High-Idle Engine Speed	3,200 rpm
Fuel Requirement	Ultra-low sulfur diesel
Oil Capacity	12.0 quarts (11.3 liters) with filter
Coolant Capacity	23.8 quarts (22.50 liters)
Emission Controls	Selective catalytic reduction (SCR)

TRANSMISSION: ZF 8HP75 TORQUEFLITE HD — AUTOMATIC EIGHT-SPEED (3500 ONLY)

Availability	6.4-liter HEMI V-8
Description	Adaptive electronic control, automatic or Electronic Range Select (ERS) manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear
Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.10
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Axle Ratio	4.10



TRANSMISSION: ZF 8AP430 TORQUEFLITE HD — AUTOMATIC EIGHT-SPEED

Availability	6.4-liter HEMI V-8
Description	Adaptive electronic control, automatic or Electronic Range Select (ERS) manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear
Gear Ratios	
1st	4.89
2nd	3.12
3rd	2.03
4th	1.64
5th	1.27
6th	1.00
7th	.84
8 th	.67
Reverse	3.30
Axle Ratios	3.42 (3500) or 4.44 (4500 and 5500)
PTO Capability	Left or right

TRANSMISSION: ZF 8AP850 TORQUEFLITE HD — AUTOMATIC EIGHT-SPEED

Availability	6.7-liter I-6 Cummins turbo diesel
Description	Adaptive electronic control, automatic or Electronic Range Select (ERS) manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear
Gear Ratios	
1st	4.89
2nd	3.12
3rd	2.03
4th	1.64
5th	1.27
6th	1.00
7 th	.83
8 th	.64
Reverse	4.25
Axle Ratios	4.10 (3500) or 4.44 (4500 and 5500)
PTO Capability	Left or right



TRANSFER CASE: BW 44-46, BW 44-47

Availability	Optional on 6.7-liter diesel and 6.4-liter HEMI V-8
Type	Part-time – electric shift
Operating Modes	2WD; 4WD High; Neutral; 4WD Low
Low-Range Ratio	2.64
Center Differential	None

TRANSFER CASE: BW 44-48, 44-49

Availability	6.7-liter diesel high output
Type	Part-time with electric shift
Operating Modes	2WD; 4WD High; Neutral; 4WD Low
Low-Range Ratio	2.64
Center Differential	None

AXLES

Front (4x4)	10.5-in. beam front axle with center disconnect (4500 and 5500)
Rear	12.0-in. beam rear axle (4500 and 5500)

ELECTRICAL SYSTEM

Alternator	
Rating	220-amp included with 6.4-liter HEMI V8 and 6.7-liter diesel Dual (220 and 180) optional on 6.4-liter HEMI V-8 Dual 220-amp optional on 6.7-liter diesel
Battery	
Description	Group 65, maintenance-free, 730 CCA on 6.4-liter HEMI V-8 Dual Group 65, maintenance-free, 730 CCA on 6.7-liter diesel

SUSPENSION 3500

Model	4x2	4x4
Front	Three-link with track bar, coil springs, stabilizer bar, solid axle	Three-link with track bar, coil springs, stabilizer bar, solid axle
Rear	Two-stage longitudinal leaf solid axle	Two-stage longitudinal leaf solid axle



SUSPENSION 4500/5500

Model	4x2	4x4
Front	Five-link with track bar, coil springs, stabilizer bar, solid axle	Five-link with track bar, coil springs, stabilizer bar, solid axle
Rear	Two-stage longitudinal leaf solid axle	Two-stage longitudinal leaf solid axle

BRAKES 3500

Front	
Size and Type	14.17 x 1.54 (359.9 x 39.1) disc with twin-piston pin-slider caliper and ABS
Rear	
Size and Type	14.09 x 1.34 (357.9 x 34.0) disc with twin-piston pin-slider caliper and ABS
Power-Assist Type	Dual-rate, tandem diaphragm vacuum (gas) Hydro-boost

BRAKES 4500/5500

Front	
Size and Type	15.35 x 1.54 (390 x 39) disc with twin-piston pin-slider caliper and ABS
Rear	
Size and Type	15.35 x 1.54 (390 x 39) disc with twin-piston pin-slider caliper and ABS
Power-Assist Type	Hydro-boost

STEERING

Power Assist	Hydraulic assist
--------------	------------------

EXTERIOR DIMENSIONS

REGULAR CAB 60 CA SRW (3500)

Regular Cab 60 CA SRW (3500)	4x2	4x4
Wheelbase (nominal)	143.3 (3,639)	143.3 (3,639)
Track Width – Front	67.6 (1,716)	67.6 (1,716)
Track Width – Rear	67.0 (1,703)	67.0 (1,703)



Regular Cab 60 CA SRW (3500)	4x2	4x4
Overall Length	235.3 (5,977)	235.3 (5,977)
Overall Width	82.6 (2,099)	82.6 (2,099)
Overall Height	80.9 (2,055)	80.9 (2,055)
Ground Clearance w/o Skid Plate	13.7 (347)	NA
Ground Clearance w/ Skid Plate	NA	13.7 (347)
Axle to Ground – Front	9.4 (240)	9.4 (240)
Axle to Ground – Rear	8.7 (221)	8.7 (221)
Rear of Frame to Ground	36.3 (922)	36.3 (922)
Approach Angle (degrees)	22.2	22.2
Departure Angle (degrees)	27.5	27.5
Ramp Breakover Angle w/o Skid Plate (degrees)	21.8	21.8
Ramp Breakover Angle w/ Skid Plate (degrees)	N/A	21.8

CREW CAB 60 CA SRW (3500)

Crew Cab 60 CA SRW (3500)	4x2	4x4
Wheelbase (nominal)	172.2 (4,373)	172.2 (4,373)
Track Width – Front	67.6 (1,716)	67.6 (1,716)
Track Width – Rear	67.0 (1,703)	67.0 (1,703)
Overall Length	264.2 (6,710)	264.2 (6,710)
Overall Width	82.6 (2,099)	82.6 (2,099)
Overall Height	80.6 (2,046)	80.6 (2,046)
Axle to Ground – Front	9.4 (238)	9.4 (238)
Axle to Ground – Rear	8.7 (220)	8.7 (220)
Rear of Frame to Ground	35.7 (906)	35.7 (906)
Approach Angle (degrees)	22.5	22.5
Departure Angle (degrees)	26.7	26.7
Ramp Breakover Angle w/o Skid Plate (degrees)	19.6	NA
Ramp Breakover Angle w/ Skid Plate (degrees)	NA	19.6



Crew Cab 60 CA SRW (3500)	4x2	4x4
Ground Clearance w/o Skid Plate	13.3 (339)	13.3 (339)
Ground Clearance w/ Skid Plate	NA	13.3 (339)

REGULAR CAB 60 CA DRW (3500)

Regular Cab 60 CA DRW (3500)	4x2	4x4
Wheelbase (nominal)	143.5 (3,645)	143.5 (3,645)
Track Width – Front	69.6 (1,768)	69.6 (1,768)
Track Width – Rear	71.9 (1,825)	71.9 (1,825)
Overall Length	235.3 (5,977)	235.3 (5,977)
Overall Width	92.2 (2,341)	92.2 (2,341)
Overall Height	80.2 (2,036)	80.2 (2,036)
Axle to Ground – Front	8.6 (219)	8.6 (219)
Axle to Ground – Rear	8.0 (208)	8.0 (208)
Rear of Frame to Ground	35.9 (911)	35.9 (911)
Approach Angle (degrees)	20.4	20.4
Departure Angle (degrees)	26.9	26.9
Ramp Breakover Angle w/o Skid Plate (degrees)	20.7	20.7
Ramp Breakover Angle w/ Skid Plate (degrees)	N/A	20.7
Ground Clearance w/o Skid Plate	12.9 (328)	NA
Ground Clearance w/ Skid Plate	NA	12.9 (328)

REGULAR CAB 84 CA DRW (3500)

Regular Cab 84 CA DRW (3500)	4x2	4x4
Wheelbase (nominal)	167.3 (4,249)	167.3 (4,249)
Track Width – Front	69.6 (1,768)	69.6 (1,768)
Track Width – Rear	71.9 (1,825)	71.9 (1,825)
Overall Length	259.3 (6,586)	259.3 (6,586)
Overall Width	92.2 (2,341)	92.2 (2,341)
Overall Height	79.9 (2,029)	79.9 (2,029)



Regular Cab 84 CA DRW (3500)	4x2	4x4
Axle to Ground – Front	8.7 (222)	8.7 (222)
Axle to Ground – Rear	8.0 (203)	8.0 (203)
Rear of Frame to Ground	34.9 (886)	34.9 (886)
Approach Angle (degrees)	21.0	21.0
Departure Angle (degrees)	25.7	25.7
Ramp Breakover Angle w/o Skid Plate (degrees)	17.1	NA
Ramp Breakover Angle w/ Skid Plate (degrees)	NA	18.1
Ground Clearance w/o Skid Plate	12.7 (322)	12.7 (322)
Ground Clearance w/ Skid Plate	NA	12.7 (322)

CREW CAB 60 CA DRW (3500)

Crew Cab 60 CA DRW (3500)	4x2	4x4
Wheelbase (nominal)	172.4 (4,379)	172.4 (4,379)
Track Width – Front	69.6 (1,768)	69.6 (1,768)
Track Width – Rear	71.9 (1,825)	71.9 (1,825)
Overall Length	264.2 (6,710)	264.2 (6,710)
Overall Width	92.2 (2,341)	92.2 (2,341)
Overall Height	79.6 (2,022)	79.6 (2,022)
Axle to Ground – Front	8.5 (217)	8.5 (217)
Axle to Ground – Rear	8.0 (202)	8.0 (202)
Rear of Frame to Ground	34.3 (872)	34.3 (872)
Approach Angle (degrees)	21.0	21.0
Departure Angle (degrees)	25.1	25.1
Ramp Breakover Angle w/o Skid Plate (degrees)	18.0	NA
Ramp Breakover Angle w/ Skid Plate (degrees)	NA	18.0
Ground Clearance w/o Skid Plate	12.4 (316)	12.4 (316)
Ground Clearance w/ Skid Plate	NA	12.4 (316)



REGULAR CAB 4x2 / 4x4 (4500/5500)

Regular Cab 4x2 / 4x4 (4500/5500)	60 CA	84 CA
Wheelbase (nominal)	144.6 (3,674)	168.7 (4,284)
Track Width – Front	77.1 (1,958)	77.1 (1,958)
Track Width – Rear	73.6 (1,870)	73.6 (1,870)
Overall Length	236.3 (6,001)	260.2 (6,610)
Overall Width	93.2 (2,368)	93.2 (2,368)
Overall Height	81.7 (2,075)	81.5 (2,071)
Axle to Ground – Front	8.7 (221)	8.7 (221)
Axle to Ground – Rear	8.0 (202)	8.0 (202)
Rear of Frame to Ground	36.4 (925)	36.2 (920)
Approach Angle (degrees)	25.4	25.7
Departure Angle (degrees)	27.7	27.5
Ramp Breakover Angle w/o Skid Plate (degrees)	22.6	NA
Ramp Breakover Angle w/ Skid Plate (degrees)	22.6	20.8
Ground Clearance w/o Skid Plate	13.7 (348)	13.5 (344)
Ground Clearance w/ Skid Plate	13.7 (348)	13.5 (344)

REGULAR CAB 4x2 / 4x4 (4500/5500)

Regular Cab 4x2 / 4x4 (4500/5500)	108 CA	120 CA
Wheelbase (nominal)	192.6 (4,893)	204.4 (5,191)
Track Width – Front	77.1 (1,958)	77.1 (1,958)
Track Width – Rear	73.6 (1,870)	73.6 (1,870)
Overall Length	284.3 (7,221)	296.3 (7,525)
Overall Width	93.2 (2,368)	93.2 (2,368)
Overall Height	81.5 (2,071)	81.4 (2,068)
Axle to Ground – Front	8.7 (221)	8.7 (221)
Axle to Ground – Rear	8.1 (206)	8.1 (206)
Rear of Frame to Ground	36.9 (936)	36.6 (930)



Regular Cab 4x2 / 4x4 (4500/5500)	108 CA	120 CA
Approach Angle (degrees)	25.7	25.8
Departure Angle (degrees)	28.2	27.6
Ramp Breakover Angle w/o Skid Plate (degrees)	20.2	NA
Ramp Breakover Angle w/ Skid Plate (degrees)	20.2	19.6
Ground Clearance w/o Skid Plate	13.6 (345)	13.5 (342)
Ground Clearance w/ Skid Plate	13.6 (345)	13.5 (342)

CREW CAB 4x2 / 4x4 (4500/5500)

Crew Cab 4x2 / 4x4 (4500/5500)	60 CA	84 CA
Wheelbase (nominal)	173.5 (4,407)	197.5 (5,017)
Track Width – Front	77.1 (1,958)	77.1 (1,958)
Track Width – Rear	73.6 (1,870)	73.6 (1,870)
Overall Length	265.2 (6,735)	289.2 (7,345)
Overall Width	93.2 (2,368)	93.2 (2,368)
Overall Height	81.4 (2,068)	81.4 (2,068)
Axle to Ground – Front	8.7 (220)	8.6 (219)
Axle to Ground – Rear	8.1 (206)	8.1 (206)
Rear of Frame to Ground	35.5 (901)	36.7 (932)
Approach Angle (degrees)	25.4	25.5
Departure Angle (degrees)	27.3	28.0
Ramp Breakover Angle w/o Skid Plate (degrees)	20.4	NA
Ramp Breakover Angle w/ Skid Plate (degrees)	20.4	19.9
Ground Clearance w/o Skid Plate	13.5 (342)	13.5 (342)
Ground Clearance w/ Skid Plate	13.5 (342)	13.5 (342)



ACCOMMODATIONS

REGULAR CAB 60 CA SRW (3500)

Regular Cab 60 CA SRW (3500)	4x2	4x4
Seating Capacity, F/R	3/-	3/-
Front		
Headroom	39.8 (1,011)	39.8 (1,011)
Legroom	40.9 (1,040)	40.9 (1,040)
Shoulder Room	65.9 (1,675)	65.9 (1,675)
Hip Room	62.9 (1,598)	62.9 (1,598)
Seat Travel	9.1 (230)	9.1 (230)
Recliner Range (degrees)	59.0	59.0
Interior Volume		
Front – cu. ft. (cu. m)	62.2 (1.8)	62.2 (1.8)

CREW CAB 60 CA SRW (3500)

Crew Cab 60 CA SRW (3500)	4x2	4x4
Seating Capacity, F/R	3/3	3/3
Front		
Headroom	40.9 (1,038)	40.9 (1,038)
Legroom	40.9 (1,040)	40.9 (1,040)
Shoulder Room	65.9 (1,675)	65.9 (1,675)
Hip Room	62.9 (1,598)	62.9 (1,598)
Seat Travel	9.1 (230)	9.1 (230)
Recliner Range (degrees)	59.0	59.0
Rear		
Headroom	39.8 (1,010)	39.8 (1,010)
Legroom	40.2 (1,022)	40.2 (1,022)
Shoulder Room	65.6 (1,666)	65.6 (1,666)
Hip Room	62.7 (1,593)	62.7 (1,593)



Crew Cab 60 CA SRW (3500)	4x2	4x4
Interior Volume		
Front – cu. ft. (cu. m)	63.9 (1.8)	63.9 (1.8)
Rear – cu. ft. (cu. m)	60.7 (1.7)	60.7 (1.7)

REGULAR CAB 60 CA DRW (3500)

Regular Cab 60 CA DRW (3500)	4x2	4x4
Seating Capacity, F/R	3/–	3/–
Front		
Headroom	39.8 (1,011)	39.8 (1,011)
Legroom	40.9 (1,040)	40.9 (1,040)
Shoulder Room	65.9 (1,675)	65.9 (1,675)
Hip Room	62.9 (1,598)	62.9 (1,598)
Seat Travel	9.1 (230)	9.1 (230)
Recliner Range (degrees)	59.0	59.0
Interior Volume		
Front – cu. ft. (cu. m)	62.2 (1.8)	62.2 (1.8)

REGULAR CAB 84 CA DRW (3500)

Regular Cab 84 CA DRW (3500)	4x2	4x4
Seating Capacity, F/R	3/–	3/–
Front		
Headroom	39.8 (1,011)	39.8 (1,011)
Legroom	40.9 (1,040)	40.9 (1,040)
Shoulder Room	65.9 (1,675)	65.9 (1,675)
Hip Room	62.9 (1,598)	62.9 (1,598)
Seat Travel	9.1 (230)	9.1 (230)
Recliner Range (degrees)	59.0	59.0
Interior Volume		
Front – cu. ft. (cu. m)	62.2 (1.8)	62.2 (1.8)



CREW CAB 60 CA DRW (3500)

Crew Cab 60 CA DRW (3500)	4x2	4x4
Seating Capacity, F/R	3/3	3/3
Front		
Headroom	40.9 (1,038)	40.9 (1,038)
Legroom	40.9 (1,040)	40.9 (1,040)
Shoulder Room	65.9 (1,675)	65.9 (1,675)
Hip Room	62.9 (1,598)	62.9 (1,598)
Seat Travel	9.1 (230)	9.1 (230)
Recliner Range (degrees)	59.0	59.0
Rear		
Headroom	39.8 (1,010)	39.8 (1,010)
Legroom	40.2 (1,022)	40.2 (1,022)
Shoulder Room	65.6 (1,666)	65.6 (1,666)
Hip Room	62.7 (1,593)	62.7 (1,593)
Interior Volume		
Front – cu. ft. (cu. m)	63.9 (1.8)	63.9 (1.8)
Rear – cu. ft. (cu. m)	60.7 (1.7)	60.7 (1.7)

REGULAR CAB 4x2 / 4x4 (4500/5500)

Regular Cab 4x2 / 4x4 (4500/5500)	60 CA	84 CA
Seating Capacity, F/R	3/–	3/–
Front		
Headroom	39.8 (1,011)	38.9 (1,038)
Legroom	40.9 (1,040)	40.9 (1,040)
Shoulder Room	65.9 (1,675)	65.9 (1,675)
Hip Room	62.9 (1,598)	62.9 (1,598)
Seat Travel	9.1 (230)	9.1 (230)
Recliner Range (degrees)	59.0	59.0



Regular Cab 4x2 / 4x4 (4500/5500)	60 CA	84 CA
Interior Volume		
Front – cu. ft. (cu. m)	62.2 (1.8)	62.2 (1.8)

REGULAR CAB 4x2 / 4x4 (4500/5500)

Regular Cab 4x2 / 4x4 (4500/5500)	108 CA	120 CA
Seating Capacity, F/R	3/–	3/–
Front		
Headroom	39.8 (1,011)	39.8 (1,011)
Legroom	40.9 (1,040)	40.9 (1,040)
Shoulder Room	65.9 (1,675)	65.9 (1,675)
Hip Room	62.9 (1,598)	62.9 (1,598)
Seat Travel	9.1 (230)	9.1 (230)
Recliner Range (degrees)	59.0	59.0
Interior Volume		
Front – cu. ft. (cu. m)	62.2 (1.8)	62.2 (1.8)

CREW CAB 4x2 / 4x4 (4500/5500)

Crew Cab 4x2 / 4x4 (4500/5500)	60 CA	84 CA
Seating Capacity, F/R	3/3	3/3
Front		
Headroom	40.9 (1,038)	40.9 (1,038)
Legroom	40.9 (1,040)	40.9 (1,040)
Shoulder Room	65.9 (1,675)	65.9 (1,675)
Hip Room	62.9 (1,598)	62.9 (1,598)
Seat Travel	9.1 (230)	9.1 (230)
Recliner Range (degrees)	59.0	59.0
Rear		
Headroom	39.8 (1,010)	39.8 (1,010)
Legroom	40.2 (1,022)	40.2 (1,022)



Crew Cab 4x2 / 4x4 (4500/5500)	60 CA	84 CA
Shoulder Room	65.6 (1,666)	65.6 (1,666)
Hip Room	62.7 (1,593)	62.7 (1,593)
Interior Volume		
Front – cu. ft. (cu. m)	63.9 (1.8)	63.9 (1.8)
Rear – cu. ft. (cu. m)	60.7 (1.7)	60.7 (1.7)

###